



OFF-BOARD HIDEA EFI

€ 1.220,00 incl. VAT

MODEL HDF5



The Hidea HF5 gives you that peace of mind you need when purchasing an outboard. With Hidea's excellence in engineering, you can be assured that you are choosing an engine that will be with you for years to come. The HDF5 features a new side mounted shift lever with reduced emissions and exceptional fuel economy, this little 5hp 4-stroke is cleaner burning while also keeping your cost at the gas pump down. Also featured on the 5hp Hidea outboard is an integrated fuel tank for true grab-and-go portability. External tank connection is standard which makes adding an external fuel tank and line quick and easy.

Hidea 5hp 4-Stroke Benefits:

- Truly six layers of paint, good corrosion resistance.
- Using the US brand PPG paint, more beautiful exterior.
- Anti-watergrass design, Truly without wrapped water grass.
- Light and compact!
- Side mounted shift lever.
- Designed with proven technology
- Greatly reduced vibration for smooth and stable running at all speeds
- Greatly reduced induction noise for a quieter ride
- External tank connection available.
- CE approved

Easy Operation and Handling:

- TCI ignition for easier engine starting, quicker throttle response and smoother trolling
- Recoil starter with larger reel making manual starting fast and easy
- Shallow water drive
- Adjustable steering friction for reducing steering effort
- Newly designed holding grip and larger carrying handle
- Newly designed with full aluminum bottom cover.

Fundamentals for User Convenience and Reliability:

- Through-the-prop exhaust for a quieter ride
- Thermostatically controlled cooling system for consistent engine temperature
- Stainless steel water pump housing liner for outstanding durability
- High grade marine aluminum alloy that provides the ultimate protection against corrosion
- Zinc coating on internal water passages for superior corrosion resistance
- 1.2 liter fuel tank with fuel gauge

Suitable for

- [Fishing](#)
- [Watersport](#)
- [Recreation](#)
-

Max. power	3.6 KW (4.90 CV)	Weight	24kg
Max. RPM	4500-5500 mm	Gear Shifting	Forward - Neutral - Reverse
Motortype	4-takt	Ignition	TCI
Cylinder	1	Cooling	Water
Engine capacity	112 CC	Starting Procedure	Manual
Bore x Stroke	59x 41 mm	Operation	Rear operation
Fuel Tank Capacity 1.1 L			